

# Protect Plus



UPS VFD



Tower



**1:1** 650-850 VA



Plug & Play  
installation



## HIGHLIGHTS

- **Compact**
- **Silent operation**
- **Auto restart**
- **Low power consumption**

The Protect Plus range is the ideal solution for protecting PCs and peripherals in the home and office.

Protect Plus is easy to install and economic to run for protecting:

- IT equipment such as PCs, Media Centres and peripherals, TVs, Home Cinema systems, Satellite and Digital Terrestrial Receivers and DVD recorders and players;
- xDSL modems and routers;
- Small home appliances.

### Silent operation

The UPS is silent in operation (0dBA) thanks to its use of a fan-less design and high frequency components.

### Auto restart

The UPS automatically restarts when the mains power supply is restored, after auto power.

### ECO Line environmental protection

With energy savings in mind, the Protect Plus range features a shut-off button to reduce energy consumption during periods of prolonged inactivity.

### Features

- Reduced energy consumption and 99% efficiency.
- Can be installed on PCs, cash registers and Pos.
- Small size: With its compact shape, Protect Plus can be placed anywhere on the desk or in the home.
- Silent: Protect Plus is also suitable for protecting your non-professional digital equipment such as home cinema systems, satellite and digital terrestrial receivers, DVD and Bluray players/recorders.

### 2-YEAR WARRANTY

MODELS	PRP 650	PRP 850
POWER	650 VA/360 W	850 VA/480 W
INPUT		
Nominal voltage	220-240 Vac	
Input voltage tolerance frequency	230 Vac (+20/-25%)	
Frequency	50/60 Hz with automatic selection	
OUTPUT		
Voltage during mains operation	230 Vac (+20/-25%)	
Voltage during battery operation	230 Vac (+/- 10%)	
Frequency during battery operation	50 or 60 Hz (+/- 1 Hz)	
Waveform	Pseudo Sinusoidal	
BATTERIES		
Type	VRLA AGM maintenance-free lead based	
Recharge time	6-8 hours	
OTHER FEATURES		
Net weight (kg)	2,7	3,1
Gross weight (kg)	3	3,4
Dimensions (WxDxH) (mm)	82,5 x 228 x 207 (vertically stand)	
Packaging dimensions (WxDxH) (mm)	288 x 120 x 280	
Protections	Excessive low battery - overvoltage - short circuit	
Output sockets	2 sockets (Schuko)	
Standards	EN 62040-1-1 and Directive 2006/95/EC; EN 62040-3 EN 62040-2 and Directive 2004/108 EC	
Certificates	CE	
Operating temperature	0 °C / +40 °C	
Colour	Black	
Altitude and relative humidity	6000 m max altitude, < 95% non-condensing	
Equipment provided	user guide	

## DETAILS

